



Corresponds with requirements / specifications / products:

SAE 5W-30
API SN/CH-4
ACEA A3/B4
VW 502 00
VW 505 00
VW 503 01
VW 501 01
MB 229.3
MB 229.5
BMW Longlife-98
RENAULT RN0700
RENAULT RN0710
FORD WSS-M2C913-B

Volume:

1 L (PM0330-1)	4 L (PM0330-4)
5 L (PM0330-5)	10 L (PM0330-10)
20 L (PM0330-20)	60 L (PM0330-60)
208 L (PM0330-DR)	1000 L (PM0330-IBC)

Innovative universal premium ester-containing engine oil for modern gasoline and diesel engines with and without turbocharging. Designed based on the requirements of European car manufacturers.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/m ³	850
Viscosity at 40 °C	D 445	cSt	70.04
Viscosity at 100 °C	D 445	cSt	11.58
Viscosity index	D 2270		160
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-45
TBN	D 2896	mgKOH/g	11.19
Dynamic viscosity [cP], at -30°C, max	D 5293	°C	6600
High shear rate viscosity cP at 150°C, min	D 4741	°C	3.58

We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development.