

340 Ultimate Quality Engine Oil



Corresponds with requirements / specifications / products:

SAE 5W-40
API SN/CH-4
ACEA A3/B4
MB 229.5/229.3/226.5
JASO MA2
VOLKSWAGEN 502 00/505 00
PORSCHE A40
RENAULT RN0710/0700
BMW LL-01/-98
PSA B71 2296
FIAT 9.55535-H2/-Z2
CHRYSLER MS-10850/-10896/-12991
GM LL-A-025
GM LL-B-025

Volume:

1 L (PM0340-1)	4 L (PM0340-4)
5 L (PM0340-5)	10 L (PM0340-10)
20 L (PM0340-20)	60 L (PM0340-60)
208 L (PM0340-DR)	1000 L (PM0340-IBC)

Innovative universal ester-containing premium motor oil for modern gasoline and diesel engines with and without turbocharging, including “old” brands and high mileage. Designed based on the requirements of European producers.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/m ³	850
Viscosity at 40 °C	D 445	cSt	79.60
Viscosity at 100 °C	D 445	cSt	13.24
Viscosity index	D 2270		169
Flash point COC	D 92	°C	236
Pour point	D 97	°C	-40
TBN	D 2896	mgKOH/g	10.01
Dynamic viscosity [cP], at -30 °C, max	D 5293	°C	5728

We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development.