

345 Superior Diesel Engine Oil



Corresponds with requirements / specifications / products:

SAE 5W-30
API SN/CH-4
ACEA C2/C3
VW 505 01
BMW LL-04
MB 229.52
MB 229.51
MB 229.31
MB 226.5
GM dexos2
RENAULT RN0700
RENAULT RN0710

Volume:

1 L (PM0345-1) 5 L (PM0345-5)
20 L (PM0345-20) 60 L (PM0345-60)
208 L (PM0345-DR) 1000 L (PM0345-IBC)

Innovative universal ester-containing synthetic premium motor oil for modern diesel and gasoline engines with and without turbocharging. Especially recommended for direct injection turbodiesel engines. Designed to meet VW requirements.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/m ³	850
Viscosity at 40 °C	D 445	cSt	65.06
Viscosity at 100 °C	D 445	cSt	11.0
Viscosity index	D 2270		162
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-42
TBN	D 2896	mgKOH/g	8.90
Dynamic viscosity [cP], at -30°C, max	D 5293	°C	4835

We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development.