



Corresponds with requirements / specifications / products:

SAE 5W-30
API SN
ACEA C3
MB 229.51
VOLKSWAGEN 504 00
VOLKSWAGEN 507 00
VOLKSWAGEN TL 52 195
BMW LL-04
PORSCHE C30

Volume:

1 L (PM0350-1)	4 L (PM0350-4)
5 L (PM0350-5)	10 L (PM0350-10)
20 L (PM0350-20)	60 L (PM0350-60)
208 L (PM0350-DR)	1000 L (PM0350-IBC)

Innovative universal multigrade bi-synthetic (PAO + esters) premium motor oil for modern gasoline and diesel engines (including those with direct injection) with and without turbocharging, including those equipped with pump nozzles (Pumpe-Duse). Designed based on VW and DAIMLER requirements.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 445	kg/l	850
Viscosity at 40 °C	D 445	cSt	66.79
Viscosity at 100 °C	D 445	cSt	11.19
Dynamic viscosity at -35 °C	D 5293	cP(mPas)	6132
Viscosity index	D 2270		161
Flash point COC	D 92	°C	224
Pour point	D 97		-48
TBN	D 2896	mgKOH/g	8.81
Ignition temperature		°C	350
Mechanical impurities	D 2273		-

We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development.