

## 430 Automatic Transmission Fluid



### Corresponds with requirements / specifications / products:

GM Dexron III H  
GM Dexron III G  
GM Dexron III F  
FORD Mercon V  
FORD ESP-M2C138-CJ  
FORD ESP-M2C166-H  
ZF TE-ML 09  
ZF TE-ML 11  
ZF TE-ML 14  
MB 236.1  
ALLISON C4  
VOITH H55.6335xx (G607)  
CATERPILLAR TO-2  
Others Power Steering Fluid

### Volume:

1 L (PM0430-1)      10 L (PM0430-10)  
20 L (PM0430-20)    60 L (PM0430-60)  
208 L (PM0430-DR) 1000 L (PM0430-IBC)

A universal all-season synthetic-based transmission fluid (ATF) for automatic gearboxes, hydraulic converters, hydraulic power steering systems, car hydraulic clutches and other hydraulic devices, including the ones operating under heavy-duty conditions in trucks and off-road vehicles. It ensures a flawless operation of an automatic gearbox, guarantees minimal wear, a lasting service life of transmissions and fuel economy. It was developed on the basis of the requirements set by GM and Ford groups.

### Product Characteristics:

| Characteristics                        | Method | Unit     | Value  |
|----------------------------------------|--------|----------|--------|
| Color                                  | visual |          | RED    |
| Density at 15 °C                       | D 445  | kg/l     | 850    |
| Viscosity at 40 °C                     | D 445  | cSt      | 36.22  |
| Viscosity at 100 °C                    | D 445  | cSt      | 7.15   |
| Brookfield dynamic viscosity at -40 °C | D 2983 | cP(mPas) | 18 000 |
| Viscosity index                        | D 2270 |          | 165    |
| Flash point COC                        | D 92   | °C       | 216    |
| Pour point                             | D 97   |          | -46    |
| Ignition temperature                   |        | °C       | 350    |
| Mechanical impurities                  | D 2273 |          | -      |

We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development.