

465 Automatic Transmission Fluid



Corresponds with requirements / specifications / products:

JASO M315 Type 1A
ALLISON C4
GM Dexron VI
FORD Mercon LV
CHRYSLER ATF +4
MB 236.14
ZF TE-ML 09
BMW JWS 3309 (T-IV)
VOLVO CE 97340
NISSAN Matic S
HONDA ATF DW-1
HYUNDAI ATF SP-IV
KIA ATF SP-IV
TOYOTA ATF WS Lifetime
LEXUS ATF WS Lifetime
FIAT 9.55550-AV2

Volume:

1 L (PM0465-1) 10 L (PM0465-10)
20 L (PM0465-20) 60 L (PM0465-60)
208 L (PM0465-DR) 1000 L (PM0465-IBC)

A universal all-season synthetic transmission fluid (ATF) for automatic gearboxes, hydraulic converters, hydraulic power steering systems, car hydraulic clutches and other hydraulic devices, including the ones operating in heavy-duty conditions in trucks and off-road vehicles. It ensures a flawless operation of an automatic gearbox, guarantees minimal wear, a lasting service life of transmissions and fuel economy. It was developed on the basis of the requirements set by GM and Ford groups.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/m ³	850
Viscosity at 40 °C	D 445	cSt	28.46
Viscosity at 100 °C	D 445	cSt	5.86
Brookfield dynamic viscosity at -40 °C	D 2983	°C	9960
Viscosity index	D 2270		156
Flash point COC	D 92	°C	214
Pour point	D 97	°C	-52

We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development.