



DIESEL

G-7 UHPD BLUE

Truck Engine Oil



Corresponds with requirements / specifications / products:

Specifications:

SAE 10W-40
API CK-4/CJ-4
ACEA E6/E9
DAF (ACEA E6)
IVECO (ACEA E6)
CATERPILLAR ECF-3
CUMMINS CES 20086
DETROIT DIESEL DDC 93K222
DEUTZ DQC IV-18 LA
MAN M 3775
MB 228.31

Approval:

MACK EOS-4.5 Approval
MAN M 3477 Approval
MB Approval 228.51
RENAULT VI RLD-3 Approval
VOLVO VDS-4.5 Approval

Volume:

10 L (PM0707-10) 1000 L (PM0707-IBC)
20 L (PM0707-20)
208 L (PM0707-DR)

All-weather synthetic motor oil for heavy-duty and high-speed diesel engines of the latest generation with and without turbocharger, operating in severe conditions on low sulphur fuel. The oil has successfully passed road and laboratory tests at VOLVO, Mercedes-Benz, MAN, MACK and RENAULT centres and has their written approvals.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/l	0.87
Viscosity at 40 °C	D 445	cSt	90.93
Viscosity at 100 °C	D 445	cSt	14.40
Viscosity at -25 °C	D 5293	CP	4067
Viscosity index	D 2270		164
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-38
TBN	D 2896	mgKOH/g	10.48
Sulphate ash (% mass), max	D 874	%	1

We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development.