



DIESEL

G-10 UHPD

Truck Engine Oil



Corresponds with requirements / specifications / products:

SAE 5W-40
API CI-4/SL
ACEA E7
ACEA E4
MB 228.5
MACK EO-N
MTU Type 3
DEUTZ DQC IV-10
MAN M 3277
RENAULT RLD-2
VOLVO VDS-3

Volume:

10 L (PM0710-10) 1000 L (PM0710-IBC)
20 L (PM0710-20)
208 L (PM0710-DR)

The universal all-season synthetic engine oil for modern high-load and high-speed diesel engines with and without turbocharging, operating in harsh conditions and at low ambient temperatures.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/l	0.85
Viscosity at 40 °C	D 445	cSt	87.92
Viscosity at 100 °C	D 445	cSt	13.57
Viscosity at -30 °C	D 5293	CP	6550
Viscosity index	D 2270		157
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-45
TBN	D 2896	mgKOH/g	13.70
Sulphate ash (% mass), max	D 874	%	1.35
Noakc volatility test, mass/mass, max	D 5800	%	11

We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development.