



DIESEL

G-14 UHPD

Truck Engine Oil



Corresponds with requirements / specifications / products:

SAE 15W-40
API CK-4
ACEA E11 -22
ACEA E7 -22
ACEA E9 -16
JASO DH-2
MB 228.31
CATERPILLAR ECF-3
CUMMINS CES 20086
CUMMINS CES 20092
MAN M 3775
DETROIT DIESEL DDC 93K223
MACK EOS-4.5 Approval
RENAULT RLD-3 Approval
VOLVO VDS-4.5 Approval

Volume:

20 L (PM0714-20)
208 L (PM0714-DR)
1000 L (PM0714-IBC)

All-weather synthetic engine oil for heavy-duty and high-speed diesel engines with and without turbocharger, operating in difficult conditions and complying with the latest environmental regulations.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/l	0.87
Viscosity at 40 °C	D 445	cSt	105.68
Viscosity at 100 °C	D 445	cSt	14.40
Viscosity index	D 2270		140
Flash point COC	D 92	°C	230
Pour point	D 97	°C	-40
Density viscosity at -20 °C	D 5293	[cP](mPas)	5299
Sulphate ash	D 874	% mass	1.0
Total base no.	D 2896	mgKOH/g	10.02
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	-

We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development.