



HYDRO ISO 46 Hydraulic Oil LONGLIFE



Corresponds with requirements / specifications / products:

ISO Viscosity Grade 46
DIN 51524-2 (HLP)
ISO 11158 (HM)
ASTM D6158
AFNOR FRANCE NF E 48-603
CONESTOGA ISO 20763
EATON I-286-S
MAG CINCINNATI P-70
PARKER DENISON HF-0/-1/-2
PARKER DENISON Filterability TP 02100
SPERRY VICKERS I-286-S
US STEEL 126 / 127
GB 111118.1
SEB 181222

Volume:

10 L (PM2102-10) 20 L (PM2102-20)
60 L (PM2102-60) 208 L (PM2102-DR)
1000 L (PM2102-IBC)

All-season mineral hydraulic oil created for hydraulic devices of stationary and mobile equipment operating in standard and high operating temperatures. It was developed taking into account the requirements for industrial hydraulic systems operating in the conditions of high loads, pressures, temperatures and/or velocities.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/l	890
Viscosity at 40 °C	D 445	cSt	46.97
Viscosity at 100 °C	D 445	cSt	7.16
Viscosity index	D 2270		111
Flash point COC	D 92	°C	216
Pour point	D 97	°C	-33
Ignition temperature, not below		°C	350
Mechanical impurities	D 2273	%	-

We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development.