



MULTIFARM STOU SAE 10W-30

Engine Transmission Oil



Corresponds with requirements / specifications / products:

SAE 10W-30
API CG-4/CF-4/CE/CD/SF
API GL-4
ACEA E3
DIN 51524-3 HVLP
ZF TE-ML 06A/06B (INC. 06R)/06C/07B
FORD NEW HOLLAND 82009201/82009202/82009203
FORD WSS-M2C159-B/-C
FORD ESN-M2C86-B/-C
FORD ESN-M2C134-D
JOHN DEERE J27
JOHN DEERE J20C/D
MASSEY FERGUSON M 1139/1144/1135/1143/1145
MB 227.1/228.1
ALLISON C-4
NEW HOLLAND MAT 3525/3526
SPERRY VICKERS M-2950-S/I-286-S
EATON I-286-S/M-2950-S
CASE I H MS 1204/1206/1207/1209
CASE NEW HOLLAND MAT 3526/3525
CATERPILLAR TO-2
SAUER SUNDSTRAND DANFOSS Hydrostatic trans fluid
VOLVO WB 101
Others VOLVO WB 101, suitable for wet brakes

Volume:

10 L (PM2501-10) 208 L (PM2501-DR)
20 L (PM2501-20) 1000 L (PM2501-IBC)
60 L (PM2501-60)

A genuinely universal engine-transmission all-season semi-synthetic (HC-synthese) engine oil for modern diesel-powered engines of agricultural equipment with and without a turbocharger operating under harsh conditions as well as for manual transmissions, "wet"-type brake systems and even hydraulic systems of tractors. It was developed specially for solving particular agricultural equipment issues, ensuring the protection of the technical equipment and receiving the maximum return regardless of its operating conditions. It belongs to the STOU (Super Tractor Oil Universal) class.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/l	0.87
Viscosity at 40 °C	D 445	cSt	72.76
Viscosity at 100 °C	D 445	cSt	11.63
Viscosity at -25 °C	D 5293	CP	4186
Viscosity index	D 2270		154
Flash point COC	D 92	°C	226
Pour point	D 97	°C	-35
TBN	D 2896	mgKOH/g	11.45

We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development.