

MULTIFARM STOU *Agricultural Machinery Oil*



Corresponds with requirements / specifications / products:

SAE 10W-40,
API CG-4/CF-4/CF/CE/CD/SF, API GL-4,
ACEA E3, ALLISON C4,
DIN 51524-3 HVLP,
CASE I H MS 1204/1206/1207/1209,
CASE NEW HOLLAND MAT 3525/3526,
CATERPILLAR TO-2,
FORD ESN-M2C86-B/-C, FORD ESN-M2C134-D,
FORD WSS-M2C159-B/-C, FENDT KDM 41.2011,
FORD NEW HOLLAND 82009201/82009202/82009203,
JOHN DEERE J27/J20C/J20D,
MASSEY FERGUSON M 1135/1139/1143/1144/1145,
MB 227.1/228.1, VOLVO WB 101,
NEW HOLLAND MAT 3525/3526,
EATON M-2950-S/I-286-S,
SPERRY VICKERS M-2950-S/I-286-S,
ZF 06A/06B (INC. 06R)/06C/07B,
Others VOLVO WB 101, suitable for wet brakes,
SAUER SUNDSTRAND DANFOSS Hydro Static Trans Fluid

Volume:

10 L (PM2502-10) 208 L (PM2502-DR)
20 L (PM2502-20) 1000 L (PM2502-IBC)
60 L (PM2502-60)

A truly universal all-weather semi-synthetic motor-transmission (HC-synthes) engine oil for modern diesel engines of agricultural machinery with and without turbocharger operating in difficult conditions, as well as for mechanical transmissions, wet-type braking systems and even tractor hydraulic systems. Designed specifically to solve the specific problems of agricultural machinery, to protect the equipment and get the most out of it, regardless of the conditions of its operation. Belongs to the class STOU (abbr. From Super Tractor Oil Universal).

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/l	870
Viscosity at 40 °C	D 445	cSt	90,44
Viscosity at 100 °C	D 445	cSt	13,37
Viscosity index	D 2270		149
Flash point COC	D 92	°C	226
Pour point	D 97	°C	-35
Dynamic viscosity at -25 °C	D 5293	cP(mPas)	5186
Sulphate ash	D 874	% mass	0,8
Total base no.	D 2896	mgKOH/g	11,64
Ignition temperature		°C	350
Mechanical impurities	D 2273	%	

We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development.