



MULTI UTTO

WB IOI

Transmission Oil



Corresponds with requirements / specifications / products:

API GL-4-
DIN 51524-2
VOLVO VCE WB 101, 97303
ALLISON C4
CASE I H MS 1204/1206/1207/1209
CASE NEW HOLLAND MAT 3525
CATERPILLAR TO-2
FORD NEW HOLLAND ESN-M2C41-B
FORD NEW HOLLAND ESN-M2C86-A/-B
FORD NEW HOLLAND ESN-M2C134-A/-C/-D
JOHN DEERE J20C
MASSEY FERGUSON CMS M 1135
MASSEY FERGUSON CMS M 1141
MASSEY FERGUSON CMS M 1143
MASSEY FERGUSON CMS M 1145
NEW HOLLAND NH 420A/410B
SAUER SUNDSTRAND DANFOSS Hydro
Static Trans Fluid
KUBOTA UDT Fluid

Volume:

20 L (PM2701-20)
208 L (PM2701-DR) 1000 L (PM2701-IBC)

A universal and multi-functional mineral all-season tractor oil for farm holdings and tractors, agricultural vehicles with very high operating characteristics. Its main purpose: an oil for on-board gearboxes with a standard replacement interval. It complies with Volvo 97303 requirements. It is also suitable for mechanical gearboxes with and without synchronizers, transmissions (including power transmissions), back axles, hydraulic systems (including the ones integrated with a mechanical gearbox) and other equipment that requires Universal Tractor Transmission Oil (UTTO) grade oil. It is particularly suitable for the reduction of vibration in "wet" brake systems and power-take off.

Product Characteristics:

Characteristics	Method	Unit	Value
Density at 15 °C	D 1298	kg/m ³	870
Viscosity at 40 °C	D 445	cSt	58.28
Viscosity at 100 °C	D 445	cSt	9.48
Viscosity index	D 2270	°C	147
Flash point COC	D 92	°C	220
Pour point	D 97	°C	-45
TBN	D 2896	mgKOH/g	8.54

We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development.